

CASE STUDY

H₂S PREDICTIVE STUDY

Empowering cost-effective
H₂S management with
precise, data-driven
insights.

Read Now

2024




DIGESTER DOC
Simplifying Anaerobic Digestion.

(208) 278-2651

Sales@DigesterDoc.com

DigesterDoc.com





Project Background

Accurately predict H₂S levels to unlock innovative, tailored, and cost-effective solutions.

An anaerobic digestion facility contacted Digester Doc to address the operators' critical challenge in managing their biogas production's hydrogen sulfide (H₂S) levels. The client sought to lower operating costs and optimize their gas upgrading system by accurately predicting H₂S levels under various scenarios. Traditional H₂S removal methods had proven effective but were costly and challenging to manage. Therefore, the client commissioned Digester Doc to conduct an H₂S predictive study to explore innovative, tailored solutions.

Study Conducted 2024

Conducted by:
Abu Hashnat, PhD: Engineering Analyst | Digester Doc

H₂S poses severe risks in AD, threatening human safety and equipment integrity. Effective H₂S removal is crucial for maintaining biogas quality and reducing operational costs. Digester Doc's H₂S predictive study is vital for optimizing biogas production by analyzing feedstock characteristics, digester design, and environmental conditions. **This comprehensive approach allows for accurate prediction and efficient management of H₂S levels**, ultimately minimizing treatment costs and ensuring a safer, more cost-effective AD operations.

Problem



Before engaging Digester Doc, the AD operators had primarily relied on biological desulfurization, a conventional method for managing H₂S in biogas. This process involves the controlled introduction of small amounts of oxygen into the anaerobic digester's headspace. The oxygen supports the growth of sulfur-oxidizing bacteria, which convert H₂S into elemental sulfur, thereby reducing the overall concentration of H₂S in the biogas.

While biological desulfurization is effective to some degree, it has several limitations.



OXYGEN TOXICITY

The introduction of oxygen poses a risk to methanogens. Methanogens are highly sensitive to oxygen, and even small amounts can inhibit their activity, reducing the efficiency of production.



INCOMPLETE REDUCTION

This method alone was insufficient to reduce H₂S levels to the stringent requirements necessary for pipeline injection, necessitating additional, costly post-treatment processes.



COST & COMPLEXITY

The need to carefully control oxygen levels, monitor bacterial activity, and maintain balance in the AD adds complexity and cost, making it less feasible as a long-term solution.

At the project's onset, the AD facility's biogas contained H₂S concentrations as high as 3,500 parts per million by volume (ppmv). These levels were far above the threshold required for pipeline injection to prevent pipeline corrosion and meet safety standards.

Given these challenges, it was clear that the AD facility needed a more reliable and cost-effective approach to H₂S management.

Approach



Our Innovative Predictive Modeling

Digester Doc approached the problem by focusing on predictive modeling and leveraging a deep understanding of the biochemical processes within anaerobic digesters.

The team hypothesized that by accurately modeling the conditions within the digester—including feedstock characteristics, chemical oxygen demand (COD) conversion rates, digester design, and environmental factors—they could predict H₂S generation with high precision.

This predictive capability would allow the AD facility to anticipate H₂S levels under various operational scenarios and tailor their treatment strategies accordingly.

Predicted H₂S Levels

The modeling yielded the following predictions for H₂S concentrations at different COD conversion rates:

Max@15% conversion

3,500 ppmv

Expected@35% conversion

1,500 ppmv

Optimized@65% conversion

800 ppmv

The study involved the integration of **multiple data points**, including:

COD CONVERSION RATES

A key factor influencing H₂S production, as sulfur compounds in the feedstock are converted to H₂S during digestion. The team simulated different COD conversion rates (15%, 35%, and 65%) to predict corresponding H₂S concentrations.

DIGESTER GEOMETRY & ENVIRONMENTAL CONDITIONS

Factors such as temperature, pH, and redox potential were analyzed to understand their impact on H₂S generation.

FEEDSTOCK COMPOSITION


The sulfur content in the feedstock was a critical input for the model, affecting the potential H₂S output.

These predictions provided the AD facility operators with a clear understanding of the H₂S levels they could expect under varying conditions, enabling them to plan their treatment strategies with greater precision and confidence.

Solution




Based on the predictive model, Digester Doc recommended a two-stage treatment approach to manage H₂S levels effectively:



IN-SITU H₂S ABATEMENT

Objective: Reduce H₂S levels from 3,500 ppmv to below 100 ppmv within the digester.

Method: Applying Sulfafix, a ferric oxide-based additive, directly into the digester. Sulfafix is particularly effective in manure-based systems, which align with the facility's feedstock characteristics. The additive works by binding with hydrogen sulfide, forming stable, non-toxic compounds that are easily removed from the digester environment.



GAS POLISHING

Objective: Further reduce H₂S levels to below 100 ppmv, ensuring compliance with pipeline injection standards.

Method: Utilization of Lutum, a high-performance polishing absorbent. Lutum was selected over traditional activated carbon due to its superior capacity for H₂S adsorption and its lower frequency of media changeouts, which significantly reduces labor and maintenance costs.

Operational Parameters

Gas Flow	234	scfm
Initial H₂S	3,500	ppmv
Operating Hours	8,440	hours per year
Step-1: Target H₂S level	<100	ppmv
Step-2: Target H₂S level	<1	ppmv
Total H₂S to be removed	103	Lb/day

Although labor costs were not fully known at the time of the study, the reduced frequency of media changeouts and the simplicity of the in-situ treatment were expected to lower overall labor costs compared to traditional methods.

Results & Impact



COST EFFECTIVENESS

The two-stage treatment approach recommended by Digester Doc proved to be the most cost-effective solution for managing H₂S levels at the facility. The innovative combination of in-situ abatement and gas polishing not only met the stringent pipeline injection standards but did so at a lower operational cost than alternative methods.



ENHANCED BIOGAS QUALITY



EXTENDED EQUIPMENT LIFESPAN



INCREASED OPERATIONAL EFFICIENCY

LONG-TERM BENEFITS

Beyond immediate cost savings, the predictive study provided facility operators with a strategic advantage. By integrating predictive modeling into their operational planning, the facility is now equipped to proactively manage H₂S levels. This proactive approach reduces the likelihood of unforeseen spikes in H₂S concentration, which could otherwise require expensive emergency interventions.

Unlock critical insights for proactive management and targeted solutions against H₂S-related disruptions.



Unleash the power of precision with **tailored, data-driven solutions to conquer your H₂S challenges.**

Conclusion

Our predictive H₂S study conducted for this anaerobic digestion facility struggling to find effective H₂S management solutions underscores the value of tailored, data-driven solutions in the biogas industry.

By combining advanced predictive modeling with a deep understanding of the client's operational environment, our team delivered a cost-effective, efficient, and scalable solution for H₂S management.

Elevate your efficiency, slash operational costs, and drive your success to new heights. Let's make it happen.

Next Steps

The results from our H₂S Predictive Study offer a unique opportunity to revolutionize the industry's approach to H₂S management. The tailored, data-driven strategies outlined in the study address current challenges and lay the groundwork for sustainable, long-term operational efficiency.

Please contact our team to unlock a comprehensive view of your digester's H₂S production today. Our expert analysis and tailored recommendations can help you achieve sustainable and efficient biogas production, safeguarding your operations.

Don't let H₂S
Derail your
system.



Contact us to
optimize your
H₂S management



And take **full**
control of your
system today.






DIGESTER DOC
Simplifying Anaerobic Digestion.

H₂S PREDICTIVE STUDY

Empowering cost-effective
H₂S management with
precise, data-driven
insights.

Contact Us!



(208) 278-2651

Sales@DigesterDoc.com

DigesterDoc.com